

FORM PTO-1-90 (Modified)
(REV 11-98)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

**TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371**

BERGLUNDS P9720

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

09/508010

INTERNATIONAL APPLICATION NO.

PCT/SE98/01583

INTERNATIONAL FILING DATE

07 September 1998 (07.09.98)

PRIORITY DATE CLAIMED

07 September 1997 (07.09.97)

TITLE OF INVENTION

ELECTRONIC TONGUE

APPLICANT(S) FOR DO/EO/US

Fredrik WINQUIST and Peter WIDE (for US only)

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371 (c) (2))
 - a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ A copy of the International Search Report (PCT/ISA/210).
8. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
9. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
10. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).
11. ☐ A copy of the International Preliminary Examination Report (PCT/IPEA/409).
12. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).

Items 13 to 20 below concern document(s) or information included:

13. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
14. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
15. ☒ A **FIRST** preliminary amendment.
16. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
17. ☐ A substitute specification.
18. ☐ A change of power of attorney and/or address letter.
19. ☒ Certificate of Mailing by Express Mail
20. ☒ Other items or information:

Verified Statement Claiming Small Entity Status (2 pgs)**Preliminary Amendment (5 pgs)**

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 1.53) 097508010	INTERNATIONAL APPLICATION NO. PCT/SE98/01583	ATTORNEY'S DOCKET NUMBER BERGLUNDS P9720
----------------------------------------------------------------------	--------------------------------------------------------	----------------------------------------------------

21. The following fees are submitted:

BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :

- ☒ Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO **\$970.00**
- ☐ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO **\$840.00**
- ☐ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO **\$690.00**
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) **\$670.00**
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4) **\$96.00**

ENTER APPROPRIATE BASIC FEE AMOUNT =**CALCULATIONS PTO USE ONLY****\$970.00**

Surcharge of **\$130.00** for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (e)).

\$0.00

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE
Total claims	16 - 20 =	0	x \$18.00
Independent claims	4 - 3 =	1	x \$78.00

\$0.00**\$78.00**Multiple Dependent Claims (check if applicable). ☐**\$0.00****TOTAL OF ABOVE CALCULATIONS =****\$1,048.00**

Reduction of 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28) (check if applicable). ☒

\$524.00**SUBTOTAL =****\$524.00**

Processing fee of **\$130.00** for furnishing the English translation later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (f)).

\$0.00**TOTAL NATIONAL FEE =****\$524.00**

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). ☐

\$0.00**TOTAL FEES ENCLOSED =****\$524.00**Amount to be:
refunded

\$

charged

\$

☒ A check in the amount of **\$524.00** to cover the above fees is enclosed.

☐ Please charge my Deposit Account No. _____ in the amount of _____ to cover the above fees.
A duplicate copy of this sheet is enclosed.

☒ The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment to Deposit Account No. **08-1391** A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Hayes, Soloway, Hennessey, Grossman & Hage, PC
175 Canal Street
Manchester, NH 03101
(603) 668-1400

SIGNATURE

Norman P. Soloway

NAME

24,315

REGISTRATION NUMBER

March 6, 2000

DATE

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Appln. Of: Fredrik WINQUIST and Peter WIDE
For: ELECTRONIC TONGUE
DOCKET: BERGLUNDS P9720US

The Honorable Commissioner of Patents & Trademarks
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Dear Sir:

Prior to examination, please amend the above-identified application as follows:

IN THE CLAIMS:

Please cancel claims 2-5, without prejudice.

Please amend claims 1, 6, 7, 9, 10, 11, 12, 13, 14, 15 and 16 as follows:

1. (Amended) Measuring method, characterized in a generation of transients by applying electrical pulses to electrodes in contact with the substance to be investigated, the transients are registered[.]; (a) already from the onset for the initial transient or to end of the decline at the pulse end and the transients are then evaluated by multivariate methods[.]; or (b) with at least one measured value after the onset of the pulse and at least one measured value before the peak value and the obtained measured values are then evaluated by

multivariate methods; or (c) with at least the peak value after the onset of the pulse and the obtained measured values are then evaluated by multivariate methods; or (d) with at least one measured value after the peak of the initial pulse but before the response has fallen below 90% of the peak value and the obtained measured values are then evaluated by multivariate methods; or (e) with at least one measured value after the peak of the initial pulse but before the response has fallen below 90% or preferably 95% of the peak value, one value before the peak, and the peak value and the obtained measured values are then evaluated by multivariate methods.

6. (Amended) Method according to claim [any of the preceding claims]1, characterized in that for each pulse is one of the entities: current, voltage, energy, conductivity or effect controlled while one of the [others] other entities is registered, for example in the case of current being measured voltage or conductivity may be controlled, whereas in the case of the effect being controlled either the current or the voltage may be registered.

7. (Amended) Method according to [any of the preceding claims] claim 1, characterized in subsequent electric pulses being varied for instance to their current and/or voltage values, to their shape, or in the relation between pulse and pause between the pulses, or the frequency, alternatively the pulses may be superimposed on a rising or falling current or voltage curve.

9. (Amended) Method according to [any of the preceding claims] claim 1, characterized in the use of a number of different measure electrodes of for instance different materials or coated by different materials, or modified in different ways.

10. (Amended) Method according to [any of the preceding claims] claim 1, characterized in the use of a number of different measure electrodes placed so in relation to each other that the electrodes influence each other or that their measuring influence each [others] other's result.

11. (Amended) Method according to [any of the preceding claims] claim 1, characterized in the measuring principle being voltametric, potentiometric or conductometric, and of one, two or three electrode type.

12. (Amended) Method according to [claims any of the preceding claims] claim 1, characterized in a cyclic subsequent switching of a common current or voltage generator and/or a registration device between different measuring electrodes resulting in ample time between the pulses to each electrode to allow the influence of the previous pulse on the liquid to have ceased before next pulse arrived to the same electrode.

13. (Amended) Method according to [any of the previous claims] claim 1, characterized in a variation of the pulse frequency.

14. (Amended) Method according to [any of the previous claims] claim 1, characterized in a variation of the pulse amplitude.

15. (Amended) Method according to [any of the previous claims] claim 1, characterized in the transients being treated with suitable shape enhancing or developing techniques, as for instance derivation, integration, proportionality, etc. before the evaluation by means of multivariate recognition methods or other similar classification methods.

16. (Amended) Method according to [any of the previous claims] claim 1, characterized in a great variation of the pulse frequency, for instance 10 Hz - [100khz] 100kHz.

REMARKS

The claims have been amended to remove multiple dependencies. It is requested that the filing fee be calculated based on the claims as amended.

Respectfully submitted,



Norman P. Soloway
Attorney for Applicants
Reg. No. 24,315

[illegible]

Date of Deposit March 6, 2000

Signature of Person Mailing John H. Hogue

Name of Person Mailing Johanne Hrycuna

cb

603-668-1400

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application Of: Winqvist et al

Serial No.: 0 /

Filed:

For: Electronic tongue

Group No:

Examiner

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY
STATUS (37 CFR 1.9(c-f) and 1.27(b-d))**

With respect to the invention described in

- ☐ the specification filed herewith.
☐ application serial no. _____, filed _____
☐ patent no. _____, issued _____

I. IDENTIFICATION OF DECLARANT AND RIGHTS AS A SMALL ENTITY

I hereby declare that I am

- ☐ the owner of the small business concern identified below:
☒ an official of the small business concern empowered to act on behalf of the concern
identified below:

Name of Concern: Nordic Sensor Technologies AB

Address of Concern: Teknikringen 6, S-583 30 LINKÖPING, Sweden

and that the above identified small business concern qualifies as a small business concern as defined in 13 CFR 121.3-181 and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees under Section 41(a) and (b) of the Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

II. OWNERSHIP OF INVENTION BY DECLARANT

I hereby declare that rights under contract or law remain with and/or have been conveyed to the above identified concern **EXCEPT**, that if the rights held are not exclusive, each individual, concern or organization having rights to the invention is listed below and no rights to the invention are held (1) by any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, (2) any concern which would not

qualify as a small business concern under 37 CFR 1.9(d) or (3) a non-profit organization under 37 CFR 1.9(e).

- ☒ no such person, concern, or organization
☐ person, concerns or organizations listed below

Full Name:

Address:

- ☐ Individual ☐ Small Business Concern ☐ Non Profit Organization

III. ACKNOWLEDGMENT OF DUTY TO NOTIFY PTO OF STATUS CHANGE

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

IV. DECLARATION

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.


V. SIGNATURE

Name of Person Signing: ANDREAS BUNGE

Title of Person Signing: MANAGING DIRECTOR

Address of Person Signing: NORDIC SENSOR TECHNOLOGIES AB, TEENIKKINKUENI 6,
SE-58330 UNIKOPING, SWEDEN

SIGNATURE



DATE March 2, 2000

ELECTRONIC TONGUE

There is a growing interest in recent years for the concept of electronic noses. An electronic nose consist of an array of gas sensors with different selectivity patterns, a signal collecting unit and pattern recognition software applied to a computer. The principle is based on the fact that a large number of different compounds contributes to define a measured odor, the chemical sensor array of the electronic nose then provides a pattern output that represents a synthesis of all the components. The pattern output is given by the selectivities of the various sensors. The very essence of the electronic nose is that the combination of several specificity classes has a very large information content.

Electronic noses have already been established for qualitative analysis in various fields of the analytical chemistry, and there are already commercial instruments on the market. Due to the similarities with the human olfaction, these systems have been cited as "electronic noses". Recently, similar concepts, but for analysis in liquids, have been described. These systems are in similar ways related to the tasting sense, thus, for these concepts the terms "electronic tongue" or "taste sensor" have been coined. An electronic tongue was thus described based on a number of chalcogenid glass electrodes, combined with a pattern recognition routine for measurement of metal ions in river water (Ref 1). A more complex sensor composition consisting of glass electrodes and PVC membranes for tasting of beverages has also been described (Ref 3).

Similar concepts, denoted "taste sensors", have also been described. Thus, a LAPS (light addressable potentiometric sensor) with artificial lipid membranes as ion selective material has been described (Ref 4), as well as taste systems, based on a fibreoptical sensor array using potential sensitive dyes (Ref 5) or on a surface photovoltage technique applied to Langmuir-Blodgett films (Ref 6).

A taste sensor based on lipid/polymer membranes on a multichannel electrode has also been developed (Ref 2). This concept has been commercialized as Taste Sensing System SA401, by Anritsu Corp., Japan.

A common feature for these electronic tongues or taste sensors described, that the sensing

SUBSTITUTE SHEET (RULE 26)

Thus, these known taste sensors are not sufficiently discriminating to allow for instance quality monitoring in e.g. food processes. The variation in the response to different parameters is not sufficient and despite the use of pattern recognition methods as known from the electronic nose technique the resulting patterns are not separable with sufficient precision.

In view of the above mentioned problems encountered with known taste sensors or electronic tongues the object of the invention is to improve the pattern response to variations in tested substances. This object is achieved by a generation of transients by applying electrical pulses to electrodes in contact with the substance to be investigated. For instance voltage pulses may be applied and the current be monitored. Transients will appear at the front and at the rear of the measured current pulse. The transients or some part thereof is then registered and used for comparison purposes, either with measurements at preceding pulses to control continuity in for instance a production process or for comparison what we could call a library of previously registered values for substance detection purposes. For the purpose of simplicity we have in the following mainly discussed the initial transient, however the pulse end transient can be used in a similar manner and at times it may perhaps be of advantage to use measured values from both transients.

Normally in voltametry for instance, the very first moments when electricity is applied to the electrode is not considered at all and one normally waits for the more steady and thus more easily predictable conditions that follow. For the invention which may be employed to give an electronic tongue, it has, however, been found that the initial signal transient response obtained when electricity is applied will vary significantly when the tested substances vary and thus the pattern will also vary with different voltages, pulse wave forms and frequencies.

Contrary to known measuring the initial transients are recorded instead of the later stabilized conditions. The great variation obtained is however of great advantage in the invention (for instance an electronic) tongue were the important thing is to achieve as different patterns as possible for small changes in test substance. Whether the changes in signal response are predictable in a calculable sense of the word or not are however without interest provided that a given change result in the same recognition pattern change every time, which it does. The normal disadvantage can thus be considered as an advantage at the invention.

The use of the transients for recognition (analysis) or monitoring can be done in many different ways. The entire transient curve can be registered and processed or the values at specific times from pulse onset may be used. These values can then be treated by multivariate methods to gain the desired information or control parameters. If these are few only a few significant measured transient values may suffice either consisting of perhaps as little as one value taken after pulse onset but before the peak value, of the peak value only or of a value taken very shortly after the peak, within for instance 90% or preferably 95% of the peak value. Of course also combinations of these can be considered.

In particular when the transient measurements are used together with multivariate methods the resolution or precision may be enhanced by for instance varying the pulse amplitude, for instance the voltage at voltametry. Due to the difference in electric field strength the present substances will react, in particular move, with differing agility depending on size, binding to other substances etc.

In order to also increase the base for multivariate evaluation other parameters the pulse amplitude may be varied as for instance electrode material, pulse frequency, superimposed DC-voltage, catalytic influence and influence from other electrodes. Also different or varying pulse wave forms and/or frequencies, between which a base potential can be applied or superimposed can be considered.

The response signal, for instance the current transient at voltammetry may be measured during the forward step of a square pulse, after return to the initial condition, or both, and

if time is in good supply one may also register the equilibrium value between the transients. However one great advantage of the invention is the great speed with which a cascade of identical or differing measurements can be carried out due to the extremely short lived transients, for instance monitoring cycle time can be much shorter than control induced process variations. For the measuring so called "Phase Lock" methods can be used.

The pulse generated may have various origins, the principle may be based on measurements on current, voltage, effect, energy or conductivity, due to onset of pulses of voltage, current or combinations thereof.

The instantaneous faradic current at the electrode is related to surface concentrations and charge transfer rate constants, and exponentially to the difference of the electrode potential from the start value to the final potential. Various parts of the curve thus reflects amount and type of either charged or electroactive species in a complicated and superimposed way.

The current - time curve shape (A) due to the onset of a voltage pulse is schematically shown in figure 1.

At least four regions can be distinguished:

- a/ Incoming charged and/or redox active species starts to build up a Helmholtz layer. This region is dominated by type and amount of charged species.
- b/ Mixed region of incoming charged (dominating part) and/or redox active species
- c/ As in b above, but the reaction of redox active species is the dominating part of the current.
- d/ Equilibrium is achieved, and the current is solely based on reduction/oxidation of redoxactive species.

Curve B (transient at the end of the pulse) is essentially reversed from that of A. A different shape is, however, obtained due to the different compounds near the electrode surface.

003050-07030560

If in a further development of the invention only or mainly the first part of the transient is measured and used the advantage is gained that a very rapid testing or tasting can be carried out since the first part of the transient is of a very short duration. With the first part is here meant the first rising slope up to the peak. Possibly measurements a short time after this can also be used. However the use of the rising slope of the transient has the advantage of allowing a very rapid pulse frequency resulting in rapid control of for instance food processing. Transients and variations in the control sequences can thus be avoided by using the "taste transients". The achieving of these exceptional results are actually adverse to normal chemical testing since no stable conditions are achieved and instead the chaotic more or less unanalyzable relations are used for the analysis.

In one configuration of the invention two types of pulse voltammetry may be used, based on large amplitude pulse voltammetry and small amplitude pulse voltammetry, in the following abbreviated as LAPV and SAPV, respectively.

In LAPV, the electrode is held at a base potential, at which negligible electrode reactions occur. After a fixed waiting period, the potential is stepped to a final potential. A current will then flow to the electrode, initially sharp when a Helmholtz double layer of charged species is formed and electroactive compounds next to the electrode surface are oxidized or reduced. The current will then decay exponentially as the double layer capacitance is

charged and electroactive compounds are consumed, until the diffusion limited faradic current remains. The size and shape of the transient response reflects amount and diffusion coefficients of both electroactive and charged compounds in the solution. When the electrode potential is stepped back to its start value, similar but opposite reactions occur.

In the SAPV, a slow continuous DC scan is applied to the electrode on to which small amplitude voltage pulses are superimposed. This will cause a change in the concentration profile of the electroactive species at the surface. Since only small changes in the electrode potential are considered, this will result in small perturbations in the surface concentration from its original value prior to the application of the small amplitude excitation.

When using pulsed voltammetry, information can also be obtained from AC current versus frequency curves at various potentials. The potential may vary around zero (fig 4) or be superimposed on an other arbitrary statical or dynamical potential curve (fig 6).

In continuous voltammetry, the current depends of the diffusion rate of electroactive species to the working electrode. If the stirring rate in the measurement cell is changed, also the electrode current is changed. One way to overcome this is to use microelectrodes, due to favourable diffusion profiles, an other way is to use pulse voltammetry, conductometry, effect or energy measurements.

Pulse voltametry also enables the use of macroelectrodes that can be cleaned by rather harsh methods, which often is necessary to get clean electrode surfaces. Microelectrode are much more fragile.

The invention also deals with the aspect of influencing the measured solution at one position and to make measurement at an other position, so close that measurement will be affected. This means that compounds generated at one electrode are detected (together with other compounds in the solution) by the other electrode. Since both electrodes may be operated at different potentials and pulse conditions, a very large but also very complicated information concerning the measured solution may be obtained increasing the possible variations in the transients and thus provide a big base for the pattern recognition. In case

Further developments of the invention are apparent from the subclaims and the following description of experimental tests of the invented method. The description refer to the appended drawings showing:

- The basic principle behind the electronic tongue is to combine unspecific and overlapping signal transients with pattern recognition routines. Within this invention, various pulsed voltammetric techniques can be applied to generate information when combined with a multivariate method, such as principal component analysis, partial least square fits, artificial neural nets, fuzzy logic, genetic algorithms or similar statistical or "artificial intelligent" methods. In the invention, also various curve fitting methods may be used to characterize the pulse responses obtained.

The invented method can normally be divided into four steps:

- Use of pulse voltammetry (or other electrical measurement methods) to obtain information (transient curves) ;
- Use of different electrode materials or modified electrodes or pulse voltage etc to obtain different chemical reactions varying the transients;
- Use of curve fitting methods to extract or sample information from the obtained set of transients;
- Use of various multivariate signal processing methods to interpret this thereby gained information.

Prototype variations of the invention

A prototype of an electronic tongue has been designed, based on the combination of pulse voltammetry using two types of working electrodes and principal component analysis (PCA). This electronic tongue was able to classify various samples, such as fruit juices, still drinks and milk. It was also possible to follow aging processes of milk and orange juice when stored at room temperature.

Chemicals:

The samples in the experiment consisted of 6 different brands of orange juices.

Equipment:

The experiments were carried out in a standard three electrode configuration shown in fig 3, containing a double working electrode 1, an auxiliary electrode 2 consisting of a 20 * 50 mm² plate of stainless steel, and a Ag/AgCl (KCl 3M) as reference electrode 3. The double working electrode consisted of one wire of platinum and the other of gold, both with a length of 5 mm and a diameter of 1 mm. The electrode configuration was placed in a 150 ml measurement cell 4, also containing a magnetic stirrer 5 and the cell with content was kept at room temperature. Current transient responses were measured by a potentiostat 6 connected to a PC 7 via an A/D - D/A converter. The PC was used for onset of pulses and measurement of current transient responses and to store data. Via two relays 8, the PC was also used to shift type of working electrode (gold or platinum).

All voltage referred to in the following are versus the Ag/AgCl electrode.

In general for LAPV, a measurement sequence starts by applying a potential during 470 msec., then the voltage is set again to 0 volt during the same time, whereafter the cycle starts all over. By each cycle, the applied potential is decreased by a given value. Measurement values after onset of pulse at 100 msec and 430 msec., respectively, are collected, as well as the measurement value obtained 100 msec. after offset of the pulse, making altogether 3 data points for each cycle. A typical recording is shown in Figure 4, also showing the position of the measuring points. The pulse time, L1, and time between pulses, L2, are also indicated in the figure.

For the SAPV, the potential is scanned from a start value to a final value, and small voltage pulses are superimposed. Each cycle starts by decreasing the potential with a step value during 180 msec., followed by increasing the potential with a superimposed value during 180 msec. Measuring points are collected 100 msec after onset of the step potential and 100 msec after onset of the superimposed potential. The difference between these two measurement points is also taken as a data point, making altogether 3 data points collected for each cycle. A typical recording is shown in Figure 5, also showing the position of the measuring points. The pulse time, L1, and time between pulses, L2, are also shown in the figure.

Data analysis:

Principal component analysis on the data obtained was performed with a commercial software.

Results obtained of the prototype:

An experimental series were performed, the samples investigated are shown in Table 1. A PCA plot for the whole series of samples is shown in Figure 6. The samples were normalized by dividing by mean in each column. A clear separation between the various samples can be seen.

In the above experiment the concept of an electronic tongue based on the invention demon-

A further development of the concept is also to use other metals as working electrodes, such as palladium, rhodium and iridium or in some other way change the electrode properties by e.g. surface modifications, use of alloys, etc.... Furthermore, electrodes and setups may be used where the measuring electrodes or special electrodes influence the tested liquid. The invention is not limited to liquid matter since solid matters can be tasted by wetting and then testing.

Alternatively the pump may comprise a screw in a cylinder, in the wall of which the electrodes are arranged.

To start with identical electrodes may be arranged in the feed direction of the pump. If the electrodes consume some molecules in the test sample a reaction decline from electrode to electrode can be measured, or if the electrodes instead leads to an increase in a substance

a reaction increase will be detected. This decline or increase may also constitute a part of the recognition pattern.

Secondly the identical electrodes may serve as reserves for each other so that even if one or indeed several become clogged or destroyed the redundant system can continue to measure, but preferably with an indication that all is not well with the cell.

In the case with a screw like brush element centrally in the taste cell, the center of the brush element may constitute auxiliary or reference electrode with the working electrodes on the cylinder wall. The electrodes on the wall may be constituted by circles rendering them rather unsensitive to variations in the measured sample. Also this makes it possible to fabricate a very rugged cell body in a simple way by simply arranging alternating cylindric conductive and insulating rings on top of each other. The electrodes may instead have an axial extension.

Preferably the feeding speed of the pump is kept constant at each test and the in tests that are to be comparable.

If the electrode is not continuous around a rotor measuring deviation may occur when the brush passes and shields the electrode. by synchronizing the rotation with the pulse frequency this effect can be made invisible.

00503040:063300

Table 1

Sample number	Sample type	Sample number	Sample type	Sample number	Sample type
1	Ph1	16	M4	31	OC4
2	Ph2	17	M5	32	OA3
3	Ph3	18	M6	33	OA4
4	Ph4	19	OE1	34	OB3
5	Ph5	20	OE2	35	OB4
6	OA1	21	OE3	36	SA1
7	OA2	22	OF1	37	SA2
8	OB1	23	OF2	38	SA3
9	OB2	24	OF3	39	SB1
10	OC1	25	OD1	40	SB2
11	OC2	26	OD2	41	SB3
12	OC3	27	OD3		
13	M1	28	A1		
14	M2	29	A2		
15	M3	30	A3		

Table 1

The experimental series carried out consecutively. The samples are:

Phosphate buffer at pH 7.0: Ph

Orange juice: OA, OB, OC, OD, OE, OF

Milk: M

Apple juice: A

Orange still drink: SA, SB

References

- [1]C. Di Natale, F. Davide, A. D'Amico, A. Legin, A. Rudinitskaya, B.L. Selezenev and Y. Vlasov, "Applications of an electronic tongue to the environmental control", Technical digest of Eurosensors X, Leuven, Belgium (1996) 1345-1348.
- [2]K. Toko, "Taste sensor with global selectivity", Materials Science and Engineering C4 (1996) 69-82.
- [3]A. Legin, A. Rudinitskaya, Y. Vlasov, C. Di Natale, F. Davide, A. D'Amico, "Tasting of beverages using an electronic tongue based on potentiometric sensor array", Technical digest of Eurosensors X, Leuven, Belgium (1996) 427-430.
- [4]Y. Sasaki, Y. Kanai, H. Ushida and T. Katsube, "Higly sensitive taste sensor with a new differential LAPS method", Sensors and Actuators B 24-25 (1995) 819-822.
- [5]S. Yamakawa and A. Yamaguchi, "Optical responses of potential-sensitive dye/PMMA coatings to taste solutions", Sensors and Materials 7, 4 (1995) 271-280.
- [6]Y. Kanai, M. Shimizu, H. Uchida, H. Nakahara, C.G. Zhou, H. Maekawa and T. Katsube, "Integrated taste sensor using surface photovoltage technique", Sensors and Actuators B 20 (1994) 175-179.

CLAIMS

1. Measuring method, **characterized in** a generation of transients by applying electrical pulses to electrodes in contact with the substance to be investigated, the transients are registered, already from the onset for the initial transient before the later stabilized conditions or to end of the decline at the pulse end and the transients are then evaluated by multivariate methods.

2. Measuring method, **characterized in** a generation of transients by applying electrical pulses to electrodes in contact with the substance to be investigated, the transients before the later stabilized conditions are registered, with at last one measured value after the onset of the pulse and at least one measured value before the peak value and the obtained measured values are then evaluated by multivariate methods.

3. Measuring method, **characterized in** a generation of transients by applying electrical pulses to electrodes in contact with the substance to be investigated, the transients before the later stabilized conditions are registered, with at last the peak value after the onset of the pulse and the obtained measured values are then evaluated by multivariate methods.

4. Measuring method, **characterized in** a generation of transients by applying electrical pulses to electrodes in contact with the substance to be investigated, the transients before the later stabilized conditions are registered, with at last one measured value after the peak of the initial pulse but before the response has fallen below 90% of the peak value and the obtained measured values are then evaluated by multivariate methods.

5. Measuring method, **characterized in** a generation of transients by applying electrical pulses to electrodes in contact with the substance to be investigated, the transients before the later stabilized conditions are registered, with at last one measured value after the peak of the initial pulse but before the response has fallen below 90% or preferably 95% of the peak value, one value before the peak, and the peak value and the obtained measured values are then evaluated by multivariate methods.

29 -10- 1999

6. Method according to claim any of the preceding claims, **characterized in** that for each pulse is one of the entities: current, voltage, energy, conductivity or effect controlled while one of the others entities is registered, for example in the case of current being measured voltage or conductivity may be controlled, whereas in the case of the effect being controlled either the current or the voltage may be registered.

7. Method according to any of the preceding claims, **characterized in** subsequent electric pulses being varied for instance to their current and/or voltage values, to their shape, or in the relation between pulse and pause between the pulses, or the frequency, alternatively the pulses may be superimposed on a rising or falling current or voltage curve.

8. Method according to preceding claim 7, **characterized in** the variation of at least two parameters one electric and one other, providing a two dimensional response pattern.

9. Method according to any of the preceding claims, **characterized in** the use of a number of different measure electrodes of for instance different materials or coated by different materials, or modified in different ways.

10. Method according to any of the preceding claims, **characterized in** the use of a number of different measure electrodes placed so in relation to each other that the electrodes influence each other or that their measuring influence each others result.

11. Method according to any of the preceding claims, **characterized in** the measuring principle being voltametric, potentiometric or conductometric, and of one, two or three electrode type.

12. Method according to claims any of the preceding claims, **characterized in** a cyclic subsequent switching of a common current or voltage generator and/or a registration device between different measuring electrodes resulting in ample time between the pulses to each electrode to allow the influence of the previous pulse on the liquid to have ceased before next pulse arrives to the same electrode.

13. Method according to any of the previous claims, **characterized in** a variation of the pulse frequency.

14. Method according to any of the previous claims, **characterized in** a variation of the pulse amplitude.

15. Method according to any of the previous claims, **characterized in** the transients being treated with suitable shape enhancing or developing techniques, as for instance derivation, integration, proportionality, etc. before the evaluation by means of multivariate recognition methods or other similar classification methods.

16. Method according to any of the previous claims, **characterized in** a great variation of the pulse frequency, for instance 10 Hz - 100kHz.

17. Electronic tongue, **characterized in** comprising a pulse generator coupled to electrodes for the contact with the substance that is to be investigated, a registration device for registering the transients obtained at the applying of the pulses and a computer for evaluation of the transients with multivariate pattern recognition methods.

18. Electronic tongue, **characterized in** the computer being coupled also to control the pulses to their size shape or frequency etc. or to interact between the pulse generated and the measured response.

19. Measuring or tasting tongue or cell **characterized in** comprising a pump housing in which a pump element is rotatable to cause a flow of the test specimen through the housing, the rotor being provided with a brush or rubber seal that sweeps clean electrodes arranged in the housing wall.

20. Measuring testing cell or tongue according to claim 19, **characterized in** a constant speed during testing.




Fig. 1

SUBSTITUTE SHEET (RULE 26)





Fig. 2

SUBSTITUTE SHEET (RULE 26)

Fig. 3



Measurement cell

SUBSTITUTE SHEET (RULE 26)




Fig. 4

SUBSTITUTE SHEET (RULE 26)






Fig. 5

SUBSTITUTE SHEET (RULE 26)

09508010-050800

[illegible]

0257



DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

Attorney Docket No: BERGLUNDS P9720

First Named Inventor: Fredrik Winqvist

Complete if known: Serial No: 09/508,010 Filing Date: March 6, 2000

Group Art Unit: _____ Examiner: _____

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled Electronic tongue

_____, the specification of which: ☐ is attached hereto or ☐ was filed on _____ as application Serial No. _____, and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, S. 1.56(a).

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application for patent or inventor's certificate or of any PCT international application having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s):

<u>Prior Foreign Application(s):</u>			<u>Priority Claimed</u>	<u>Certified Copy Attached</u>
<u>9703215-5</u>	<u>Sweden</u>	<u>September 09, 1997</u>	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
(Number)	(Country)	(Month/Day/Year Filed)		
_____	_____	_____	<input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Yes <input type="checkbox"/> No
(Number)	(Country)	(Month/Day/Year Filed)		

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below:

Application No: _____ Filing Date: _____

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

<u>PCT/SE98/01583</u>	<u>September 09, 1998</u>	
US Parent Application or PCT	Parent Filing Date	Parent Patent Number
Parent Number		(if applicable)

And I hereby appoint HAYES, SOLOWAY, HENNESSEY, GROSSMAN & HAGE, P.C., a firm composed of Oliver W. Hayes, Reg. No. 15,867; Norman P. Soloway, Reg. No. 24,315; William O. Hennessey, Reg. No. 32,032; Susan H. Hage, Reg. No. 29,646; Steven J. Grossman, Reg. No. 35,001; Christopher K. Gagne, Reg. No. 36,142; and Edmund Paul Pfleger, Reg. No. 41,252, or any of them, of 175 Canal Street, Manchester, New Hampshire 03101 (Telephone: 603-668-1400) my attorneys with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent Office connected therewith.

Please direct all future correspondence in connection with this application to the attention of Norman P. Soloway HAYES, SOLOWAY, HENNESSEY, GROSSMAN & HAGE, P.C., 175 Canal Street, Manchester, New Hampshire 03101 (Telephone: 603-668-1400).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor: Fredrik Winqvist

First Inventor's signature Fredrik Winqvist Date March 30, 2000

Residence: Heidenstams gata 34, 584 37 Linköping, Sweden

Citizenship: Sweden

Post Office Address: Same as residence

Full name of second joint inventor: Peter Wide

Second Inventor's signature Peter Wide Date April 3, 2000

Residence: Järsta 3, 681 93 Kristinehamn, Sweden

Citizenship: Sweden

Post Office Address: Same as residence